



ދިވެހިރާއްޖޭގެ ބަނޑުޅި ދިވެހިރާއްޖޭގެ ބަނޑުޅި

Maldives Meteorological Service

ޖެނެރަލް ސެކްޝަން ޕްރޮޖެކްޓް ޕްރޮޖެކްޓް

<p>ޖެނެރަލް ސެކްޝަން ޕްރޮޖެކްޓް ޕްރޮޖެކްޓް</p>	<p>ޖެނެރަލް ސެކްޝަން ޕްރޮޖެކްޓް ޕްރޮޖެކްޓް</p>	<p>ޖެނެރަލް ސެކްޝަން ޕްރޮޖެކްޓް ޕްރޮޖެކްޓް</p>	<p>#</p>
<p>Camera Features</p> <p>Sensor Size 22mm x 11.88mm (Super 35).</p> <p>RAW Resolution 12-bit RAW files recorded at 4000 x 2160</p> <p>Shooting Resolutions 4K RAW at 4000 x 2160. ProRes at 3840 x 2160 and 1920 x 1080.</p> <p>Frame Rates 4K RAW at 4000 x 2160p 23.98, 24, 25, 29.97, 30, Ultra HD 2160p23.98, 24, 25, 29.97, 30, HD 1080p23.98, 24, 25, 29.97, 30.</p> <p>Dynamic Range 12 stops.</p> <p>Focus Focus button turns on peaking, plus auto focus on active lenses.</p> <p>Iris Control Iris button adjusts iris settings on compatible lenses so no pixel is clipped in film mode. Scene average auto exposure in video mode.</p> <p>Lens Mount EF mount compatible with electronic iris control.</p> <p>Screen Dimensions 5" and 800 x 480 resolution.</p> <p>Metadata Support Automatic camera data and user data such as shot number, filenames and keywords.</p> <p>Screen Type Integrated LCD capacitive touchscreen.</p> <p>Controls Onscreen touch menus and physical buttons for recording and transport control.</p> <p>Microphone Integrated mono microphone.</p> <p>Speaker Integrated mono speaker.</p> <p>Mounting Options 3 x 1/4"-20 UNC thread mounting points on top of camera. 1 x 1/4"-20 UNC thread tripod mount with locator pin.</p> <p>Storage Features</p>	<p>01</p>	<p>ޖެނެރަލް ސެކްޝަން ޕްރޮޖެކްޓް ޕްރޮޖެކްޓް</p>	<p>1</p>

<p>Storage Type Removable 2.5" SSD.</p> <p>Connections SDI Video Output 1 x 6G-SDI 10-bit 4:2:2 with choice of Film or Video Dynamic Range.</p>			
<p>Camera Lens: <i>shooting video (Indoor)</i></p> <ul style="list-style-type: none"> <i>This item has to be comparable with the video camera body.</i> 	01	تاشیخ و تاشیخ	02
<p>Connections</p> <p>SDI Video Input: Switchable between SD, HD and 3G-SDI.</p> <p>SDI Video Output: 8 outputs automatically match the SDI video input.</p> <p>Multi Rate Support: Auto detection of SD, HD, 2K, or 3G-SDI.</p> <p>Reclocking: Yes</p> <p>Standards</p> <p>SD Format Support: 525/23.98 NTSC, 525/29.97 NTSC.625/25 PAL.</p> <p>HD Format Support: 720p50, 720p59.94, 720p60, 1080i50, 1080i59.94, 1080i60, 1080p23.98, 1080PsF23.98, 1080p24, 1080PsF24, 1080p25, 1080PsF25, 1080p29.97, 1080PsF29.97, 1080p30, 1080PsF30, 1080p50, 1080p59.94, 1080p60.</p> <p>2K Format Support: 2048 x 1080PsF23.98, 2048 x 1080p23.98, 2048 x 1080PsF24, 2048 x 1080p24, 2048 x 1080PsF25, 2048 x 1080p25.</p> <p>SDI Compliance: SMPTE 259M, SMPTE 292M, SMPTE 296M, SMPTE 372M, SMPTE 424M-B and SMPTE 425M</p> <p>SDI Video Rates: SDI video connections are switchable between SD, HD, and DCI 2K.</p> <p>SDI Video Sampling: 4:2:2 and 4:4:4</p> <p>SDI Audio Sampling: Television standard sample rate of 48 kHz and 24 bit.</p> <p>SDI Color Precision: 4:2:2 and 4:4:4</p> <p>SDI Color Space: YUV and RGB</p> <p>SDI Auto Switching: Automatically detects SD, HD or 3G-SDI.</p> <p>ASI Support: Yes</p>	01	تاشیخ و تاشیخ تاشیخ و تاشیخ تاشیخ و تاشیخ	03
<p>Form Factor 2.5" SSD 9.5mm</p> <p>Compressed Data Performance Read: up to 550MB/s Write: up to 500MB/s</p> <p>SATA Interface SATA III</p>	01	تاشیخ و تاشیخ تاشیخ و تاشیخ	04

